

310 Wayto Road | Schenectady, NY 12303 ● TEL: 800-283-3888 | FAX: 518-357-9636
EMAIL: moreinfo@sandellmfg.com | www.diedrichtechnologies.com

303-S WITH 15% SOLIDS

1. PRODUCT DATA

Product Name: 303-S With 15% Solids

Producer: Diedrich Technologies, A Hohmann & Barnard Company, 310 Wayto Road, Schenectady, NY 12303

Company Contact: Ken Eglin

Telephone: 800-283-3888

24-Hour Emergency Contact: CHEMTREC 800-424-9300

This product is manufactured for Commercial/Industrial use. Not recommended for: Household use.

2. HAZARDS IDENTIFICATION

GHS Ratings:

Flammable Liquids: 2

Oral Toxicity: Acute 3

Dermal Toxicity: Acute 3

Skin Irritation: 2

Eye Irritation: 2

Inhalation Toxicity: Acute 4

GHS Hazards:

H225 Highly Flammable liquid and vapor

H301 Toxic if swallowed

H311 Toxic in contact with skin

H315 Causes skin irritation

H319 Causes serious eye irritation

H332 Harmful if inhaled

GHS Precautions

P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking

P233 Keep container tightly closed

P240 Ground/bond container and receiving equipment

P241 Use explosion-proof electrical/ventilating/lighting/ or other equipment

P242 Use only non-sparking tools

P243 Take precautionary measures against static discharge

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P264 Wash hands thoroughly after handling

P270 Do not eat, drink or smoke when using this product

P271 Use only outdoors or in a well-ventilated area

P280 Wear protective gloves/protective clothing/eye protection/face protection

P312 Call a POISON CENTER or doctor/physician if you feel unwell

P321 Specific treatment (see section 4)

P322 Specific measures (see section 4)

P330 Rinse mouth

P361 Remove/Take off immediately all contaminated clothing

P362 Take off contaminated clothing and wash before reuse

P363 Wash contaminated clothing before reuse

P301+P310

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

P302+P352

IF ON SKIN: Gently wash with plenty of soap and water

P304+P340

IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing

P332+P313

IF SKIN irritation occurs: Get medical advice/attention

P337+P313

IF eye irritation persists: Get medical advice/attention

P370+P378

In case of fire: Evacuate area

P303+ P361+P353

IF ON SKIN (or hair): Remove/Take off Immediately all contaminated clothing. Rinse SKIN with water/shower

P305+P351+P338

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P403+P235

Store in a well-ventilated place. Keep cool

P405 Store locked up

P501 Dispose of contents/container according to local regulations

310 Wayto Road | Schenectady, NY 12303 ● TEL: 800-283-3888 | FAX: 518-357-9636
EMAIL: moreinfo@sandellmfg.com | www.diedrichtechnologies.com

Danger

Hazards Not Otherwise Classified: N/A

3. COMPOSITION

Chemical Name/ CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Aliphatic Solvent 64742-88-7	No Data Found	No Data Found	NIOSH: 350 mg/m ³ TWA 1,800 mg/m ³ Ceiling (15 minutes)

Specific chemical identity and percentage content of ingredients withheld as trade secret pursuant to Massachusetts regulations. Reporting requirements of section 313 title III of the superfund amendments and reauthorization act of 1986 and 10 CFR part 373 apply.

4. FIRST AID MEASURES

Inhalation: Remove to fresh air and provide oxygen if breathing is difficult. Give artificial respiration if not breathing. Get medical attention immediately.

Eye Contact: Flush with large amounts of water, lift both upper and lower eyelids frequently to assure thorough flushing under lids. Seek medical attention. If irritation persists see a physician.

Skin Contact: Wash with mild soap and water and apply skin cream. Remove contaminated clothing and launder before reuse. Discard contaminated shoes. If irritation persists see a physician.

Ingestion: If swallowed, do not induce vomiting, contact poison control center. If vomiting occurs keep head below hips to prevent aspiration of liquid into lungs, which can cause chemical pneumonitis, which can be fatal. See a physician immediately.

Notes to Physician: No data found.

5. FIRE FIGHTING MEASURES

Flammable Limits: LEL= 0.7 UEL= 6.0

Flash Point: 105°F

Extinguishing Media: Use foam, dry chemical or carbon dioxide.

Unusual Fire and Explosion Hazards: Because vapors are heavier than air they may travel along the ground or by ventilation systems far away from material handling point.

Hazardous Combustion Products: See Section 10 for a list of hazardous decomposition products for this mixture.

Fire Fighting: If evacuation of personnel is necessary, evacuate to an upwind area. Decontaminate personnel and equipment with a water wash-down after fire and smoke exposure.

Special Procedures: Use air supplied breathing apparatus. Use the procedure for fighting petroleum solvent fire.

6. ACCIDENTAL RELEASE MEASURES

Isolate the area and contain the spilled material. Persons not wearing the appropriate PPE should be removed from the area until the spill is cleaned up. Stop leak if you can do it without risk, stay upwind, and avoid run off to waterways and sewers.

SMALL SPILLS: Dike and contain. Soak up residue with absorbent, noncombustible material. Scoop into drums appropriate for disposal.

LARGE SPILLS: Avoid exposure to sparks, fire or hot metal surfaces. Eliminate possible sources of ignition. If applicable, wear appropriate respirator and other protective residue with absorbent, noncombustible material. Scoop into drum appropriate for disposal. Prevent material from entering drains, sewers or waterways.

7. HANDLING AND STORAGE

Handling Precautions: Use with adequate ventilation. Avoid prolonged or repeated contact with skin. Do not cut, puncture or weld on or near this container. Do not re-use container for any purpose until it has been commercially cleaned. Keep Container closed when not in use. **After containers have been emptied they may contain explosive and/or harmful vapors and residue.**

Storage: Keep away from heat, sparks, and open flames. Store away from oxidizing materials. **After containers have been emptied they may contain explosive and/or harmful vapors and residue.**

Regulatory Requirements: This product is classified as "Oil" under the Clean Water Act. As such it must be kept out of surface water, watercourses or sewers entering or leading to surface waters.

310 Wayto Road | Schenectady, NY 12303 ● TEL: 800-283-3888 | FAX: 518-357-9636
 EMAIL: moreinfo@sandellmfg.com | www.diedrichtechnologies.com

8. EXPOSURE CONTROL AND PERSONAL PROTECTION

Chemical Name/ CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Aliphatic Solvent 64742-88-7	No Data Found	No Data Found	NIOSH: 350 mg/m3 TWA 1,800 mg/m3 Ceiling (15 minutes)

Engineering controls: Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product. Ensure that eyewash stations and safety showers are close to the workstation location.

Ventilation Control: Local exhaust sufficient to minimize exposure to mist and fumes below permissible exposure limit. If mechanical assist is required, unit must be of an explosion proof type.

Administrative controls: No data found.

Personal Protection: As prescribed in the OSHA Standard for Personal Protective Equipment (29 CFR 1910.132), employers must perform a hazard Assessment of all workplaces to determine the need for proper protective equipment for each employee.

Protective Clothing: Protect all body parts from contact by using full chemical/solvent resistant suit with tight fitting cuffs and collar, rubber boots and full-face shield. Solvent resistant gloves such as nitrile rubber must be worn.

Eye Protection: Close fitting safety chemical goggles and face-shield must be worn.

Skin Protection: In accordance with good industrial hygiene practices, precautions should be taken to avoid skin contact. Apply Diedrich recommended skin barrier cream for additional protection.

Respiratory: A NIOSH/MSHA approved air supplied or self-contained respirator must be used if the TLV of the product or component is exceeded. Under specific conditions other NIOSH/MSHA respirators may be permitted under OSHA regulations. Consult with your safety equipment supplier.

Contaminated Equipment: Dispose of the waste in compliance with federal, state, regional, and local regulations.

9. PHYSICAL AND CHEMICAL PROPERTIES

Melting point: No Data Found
Freezing point: No Data Found
Solubility: Negligible

Boiling range: 315-380°F (157-193°C)
Flash Point: 105°F
Evaporation Rate: 0.06
Flammability: LEL= 0.7 UEL= 6.0
Appearance: Colorless liquid
Odor: Light kerosene odor
Physical State: Liquid
Vapor Pressure: No Data Found
Odor Threshold: No Data Found
Vapor Density: Lower than Air
Specific Gravity: 0.86
pH: No Data Found
Explosive Limits: LEL= 0.7 UEL= 6.0
% Volatile (by weight): 90%
Volatile Organic Components: 710 g/l
Partition Coefficient (n-Octanol/water): No Data Found
Autoignition Temperature: No Data Found
Decomposition Temperature: No Data Found
Viscosity: No Data Found
Density: No Data Found
Weight Per Gallon: 9.2 lbs.

10. STABILITY AND REACTIVITY

Stability: STABLE
Incompatibilities: No Data Found
Conditions To Avoid: Heat, sparks, open flame and fire. Keep away from pilot lights, extinguish all pilot lights in room and adjacent rooms. Be sure to search for multiple pilot lights on appliances.
Hazardous Decomposition Products: Carbon monoxide and unidentified organics may be formed during combustion.

11. TOXICOLOGICAL INFORMATION

Routes of Entry: Inhalation, skin, eyes, ingestion
Target Organs: Skin, Eyes, Stomach
Effects of Overexposure: Can lead to central nervous system depression producing effects such as headache, dizziness, nausea and loss of consciousness, and even asphyxiation.

CAS Number	Description	% Weight	Carcinogen Rating
None			Not Listed

12. ECOLOGICAL INFORMATION

Ecotoxicity: No data found.

310 Wayto Road | Schenectady, NY 12303 ● TEL: 800-283-3888 | FAX: 518-357-9636
EMAIL: moreinfo@sandellmfg.com | www.diedrichtechnologies.com

13. DISPOSAL

Disposal must be at an approved facility for compliance under RCRA Regulations for hazardous waste. Containers must have the proper labeling and be leak proof..

14. TRANSPORTATION INFORMATION

The following is for US DOT Highway transportation. Other modes/jurisdictions may have different classifications.

Agency	Proper Shipping Name	UN Number	Packaging Group	Hazard Class
US DOT	Petroleum Distillate, N.O.S.	UN 1268	III	3

15 - REGULATORY INFORMATION

No Data Found

16. OTHER INFORMATION


Date of Preparation: July 1st, 2016

Revision Date: March 16th, 2017

Hazardous Material Information System (HMIS)

Health	1
Flammability	3
Physical Hazard	0
Personal Protection	<input type="checkbox"/>

National Fire Protection Association (NFPA)



HMIS & NFPA Hazard Rating Legend

- * = CHRONIC HEALTH HAZARD
- 0 = INSIGNIFICANT
- 1 = SLIGHT
- 2 = MODERATE
- 3 = HIGH

LEGEND

0 = LEAST 1 = SLIGHT 2 = MODERATE 3 = HIGH 4 = EXTREME

N.D. = NOT DETERMINED N.A. = NOT AVAILABLE N/A = NOT APPLICABLE

DISCLAIMER: While this company believes that the data contained herein are factual and the opinions expressed are based on tests and data believed to be reliable, it is the user's responsibility to determine the safety, toxicity and suitability for his own use of the product described herein. Since the actual use by others is beyond our control, no guarantee, expressed or implied, is made by this company as to the effects of such use, the results to be obtained, or the safety and toxicity of the product, nor does this company assume any liability arising out of use, by others, of the product referred to herein. Nor is this information herein to be construed as absolutely complete since additional information may be necessary or desirable when particular or exceptional conditions or circumstances exist or because of applicable laws or governmental regulations.

REQUIRED SUPPLEMENTAL CONTRACT TERMS: Failure to obtain a property owner's written acceptance of the enclosed Required Supplemental Terms and Conditions for Restoration Contract shall release any and all of the manufacturer's express or implied warranties (including, without limitation, merchantability and fitness for particular purpose) and user shall indemnify and hold manufacturer harmless from all liability cost and expenses arising in any way from use of or contact with this product. All claims of any kind against manufacturer arising from or related to this product in any way shall be decided by binding arbitration in accordance with the Construction Industry Arbitration Rules of the American Arbitration Association.

Copyright © 2016

Diedrich Technologies is a division of



Hohmann & Barnard, Inc.
30 Rasons Court | Hauppauge, NY 11788
TEL: 800-645-0616 | FAX: 631-234-0683
EMAIL: weanchor@h-b.com | www.h-b.com