

310 Wayto Road | Schenectady, NY 12303 ● TEL: 800-283-3888 | FAX: 518-357-9636
EMAIL: moreinfo@sandellmfg.com | www.diedrichtechnologies.com

930 WHITE SCUM REMOVER

1. PRODUCT DATA

Product Name: 930 White Scum Remover

Producer: Diedrich Technologies, A Hohmann & Barnard Company, 310 Wayto Road, Schenectady, NY 12303

Company Contact: Ken Eglin

Telephone: 800-283-3888

24-Hour Emergency Contact: CHEMTREC 800-424-9300

This product is manufactured for Commercial/Industrial use. Not recommended for: Household use.

2 - HAZARDS IDENTIFICATION

GHS Ratings:

Oral Toxicity: Acute 5

Anticipated oral LD50 between 2000 and 5000 mg/kg;
Indication of significant effect in humans; any mortality at class 4; Significant clinical signs at class 4

Inhalation Toxicity: Acute 2

Gases >100 + <=500ppm, Vapors >0.5 + <=2mg/l,
Dusts & mists >0.05 + <=0.5mg/l

Skin corrosive: 1A

Destruction of dermal tissue: Exposure <3 min. Observation <1 hour, visible necrosis in at least one animal

Eye corrosive: 1

Serious eye damage: Irreversible damage 21 days after exposure, Draize score: Corneal opacity >= 3, Iritis >1.5

Carcinogen: 1B

Presumed Human Carcinogen, Based on demonstrated animal carcinogenicity

Reproductive toxin: 2

Human or animal evidence possibly with other information

GHS Hazards

- H303** May be harmful if swallowed
- H314** Causes severe skin burns and eye damage
- H318** Causes serious eye damage
- H330** Fatal if inhaled
- H350** May cause cancer
- H361** Suspected of damaging fertility or the unborn child

GHS Precautions

- P201** Obtain special instructions before use
- P202** Do not handle until all safety precautions have been read and understood
- P260** Do not breathe dust/fume/gas/mist/vapors/spray
- P264** Wash hands thoroughly after handling
- P271** Use only outdoors or in a well-ventilated area
- P280** Wear protective gloves/protective clothing/eye protection/face protection
- P281** Use personal protective equipment as required
- P284** Wear respiratory protection
- P310** Immediately call a POISON CENTER or doctor/physician
- P312** Call a POISON CENTER or doctor/physician if you feel unwell
- P320** Specific treatment is urgent (see section 4)
- P321** Specific treatment (see section 4)
- P363** Wash contaminated clothing before reuse
- P301+P330+P331**
IF SWALLOWED: Rinse mouth.
Do NOT induce vomiting
- P303+P361+P353**
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing.
Rinse skin with water/shower
- P304+P340**
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
- P305+P351+P338**
IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing
- P308+P313**
IF exposed or concerned: Get medical advice/attention
- P405** Store locked up
- P403+P233**
Store in a well ventilated place. Keep container tightly closed
- P501** Dispose of contents/container according to local regulations

310 Wayto Road | Schenectady, NY 12303 ● TEL: 800-283-3888 | FAX: 518-357-9636
EMAIL: moreinfo@sandellmfg.com | www.diedrichtechnologies.com

Danger



Hazards Not Otherwise Classified: None

3. COMPOSITION

Chemical Name/ CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Sulfuric acid 7664-93-9 12 percent	1 mg/m ³ TWA	0.2 mg/m ³ TWA (thoracic fraction)	NIOSH: 1 mg/m ³ TWA
Phosphoric acid 7664-38-2 10 percent	1 mg/m ³ TWA	3 mg/m ³ STEL 1 mg/m ³ TWA	NIOSH: 1 mg/m ³ TWA 3 mg/m ³ STEL
Ammonium bifluoride 1341-49-7 3 percent			

4. FIRST AID MEASURES

Inhalation: Remove from further exposure. For those providing assistance, avoid exposure to yourself. Use adequate respiratory protection. If respiratory irritation, dizziness, nausea, or unconsciousness occurs, seek immediate medical assistance. If breathing has stopped, a trained individual should attempt to resuscitate while getting immediate medical aid.

Eye Contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing for 15 minutes.

Skin Contact: In case of skin contact, remove contaminated clothing. Flush the skin with large amounts of water, then wash the skin with soap and water.

Ingestion: If conscious, give 2 to 3 glasses of water. Do not induce vomiting and seek medical attention immediately.

Notes to Physician: No data found.

5. FIRE FIGHTING MEASURES

Flammable Limits: LEL & UEL – N/A

Flash Point: No data available.

Extinguishing Media: Use extinguishing agent suitable for type of surrounding fire.

Unusual Fire or Explosion Hazards: No data available.

Hazardous Combustion Products: See Section 10.

Fire Fighting: If evacuation of personnel is necessary, evacuate to an upwind area. Decontaminate personnel and equipment with a water wash-down after fire and smoke exposure.

Fire Fighting: Fire fighters should wear complete protective clothing including self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

Isolate the area and contain the spilled material. Persons not wearing the appropriate PPE should be removed from the area until the spill is cleaned up. Stop leak if you can do it without risk, stay upwind, and avoid run off to waterways and sewers.

SMALL SPILLS: Prevent entry into waterways, sewers, basements or confined areas. Use a non-combustible material like vermiculite or sand to soak up the product and place into a container for later disposal.

LARGE SPILLS: Prevent entry into waterways, sewers, basements or confined areas. Dike to collect large liquid spills, collect leaking liquid in sealable compatible containers.

ACID SPILLS: Neutralize with Soda Ash (Sodium Carbonate), Hydrated Lime (Calcium Hydroxide), or Baking Soda (Sodium Bicarbonate). Cautiously neutralize remainder. Then wash away with plenty of water.

7. HANDLING AND STORAGE

Handling Precautions: Wear all appropriate Personal Protective Equipment (PPE). Wear respiratory protection or ensure adequate ventilation at all times as vapors can accumulate in confined or poorly ventilated areas. Use the product in a manner which minimizes splashes and/or the creation of dust. Keep containment closed when not in use. Do not handle or store material near heat, sparks, or open flames, or other sources of ignition.

Storage: Prevent from freezing. Store at room temperatures, i.e., 40° to 95°F (4° to 35°C)

Regulatory Requirements: No data found

310 Wayto Road | Schenectady, NY 12303 ● TEL: 800-283-3888 | FAX: 518-357-9636
 EMAIL: moreinfo@sandellmfg.com | www.diedrichtechnologies.com

8. EXPOSURE CONTROL AND PERSONAL PROTECTION

Chemical Name/ CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Sulfuric acid 7664-93-9	1 mg/m ³ TWA	0.2 mg/m ³ TWA (thoracic fraction)	NIOSH: 1 mg/m ³ TWA
Phosphoric acid 7664-38-2	1 mg/m ³ TWA	3 mg/m ³ STEL 1 mg/m ³ TWA	NIOSH: 1 mg/m ³ TWA 3 mg/m ³ STEL
Ammonium bifluoride 1341-49-7			

Engineering controls: Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product. Ensure that eyewash stations and safety showers are close to the workstation location.

Ventilation Control: Provide adequate ventilation to control airborne concentration below the exposure guidelines/limits.

Administrative controls: No data found.

Personal Protection: As prescribed in the OSHA Standard for Personal Protective Equipment (29 CFR 1910.132), employers must perform a hazard Assessment of all workplaces to determine the need for proper protective equipment for each employee.

Eye Protection: Normal industrial eye protection practices should be employed.

Skin Protection: In accordance with good industrial hygiene practices, precautions should be taken to avoid skin contact.

Respiratory: If airborne concentration limits are not met, an approved respirator must be worn.

Contaminated Equipment: Dispose of the waste in compliance with federal, state, regional, and local regulations.

9. PHYSICAL AND CHEMICAL PROPERTIES

Melting point: Not Determined

Freezing point: Not Determined

Solubility: Complete

Boiling range: 212°F (100°C)

Flash point: 999°F (999°C)

Evaporation rate: Not Determined

Flammability (UEL & LEL): N/A

Appearance: Clear, Colorless

Odor: Pungent

Physical State: Liquid

Vapor Pressure: Not Determined

Odor threshold: Not Determined

Vapor Density: Not Determined

pH: Strong Acid <1

Explosive Limits: 0%

Partition coefficient (n-Octanol/water): Not Determined

Autoignition temperature: N/A

Decomposition temperature: Not Determined

Viscosity: Not Determined

Density: 1.190115849

Weight Per Gallon: 8.5 lbs

10. STABILITY AND REACTIVITY

Stability: STABLE

Incompatibilities: Avoid contact with strong bases.

Hazardous Decomposition Products: *Note:* these are all possible decomposition products based on molecular structure of components.

- Oxides of Sulfur
- Oxides of Phosphorus
- Hydrogen or Hydrogen Fluoride
- Oxides of Nitrogen or Ammonia

Hazardous polymerization: will not occur.

11. TOXICOLOGICAL INFORMATION

Mixture Toxicity:

Oral Toxicity: 2,841.00mg/kg

Inhalation Toxicity: 0.06mg/L

Component Toxicity: 7664-38-2 Phosphoric acid

Oral: 1,530.00 mg/kg (Rat)

Dermal: 2,730.00 mg/kg (Rabbit)

Routes of entry: No data found.

Target Organs: Eyes, Skin, Respiratory System

Effects of Overexposure: Causes severe skin burns and eye damage

CAS Number	Description	% Weight	Carcinogen Rating
7664-93-9	Sulfuric acid	12	Sulfuric acid: IARC: Human carcinogen OSHA: listed

12. ECOLOGICAL INFORMATION

Ecotoxicity: No data found.

Component Ecotoxicity: Sulfuric acid 96 Hr LC50
Brachydanio rerio: >500 mg/L [static]

13. DISPOSAL

Refer to the latest federal, state, and local regulations.

310 Wayto Road | Schenectady, NY 12303 ● TEL: 800-283-3888 | FAX: 518-357-9636
EMAIL: moreinfo@sandellmfg.com | www.diedrichtechnologies.com

14. TRANSPORTATION INFORMATION

The following is for US DOT Highway transportation. Other modes/jurisdictions may have different classifications.

Agency	Proper Shipping Name	UN Number	Packaging Group	Hazard Class
US DOT	Corrosive Liquid NOS. (Sulfuric Acid Glycolic Acid)	UN1760	II	8

15 - REGULATORY INFORMATION

This listing is to highlight federal level regulation of the product. Individual states, and other nations may have further regulations not listed below.

US DOT List of Marine Pollutants (172.101 - Appendix B): None

US DOT List of Hazardous Substances and Reportable Quantities (172.101 Appendix A):

1341-49-7	Ammonium bifluoride	3%
7664-38-2	Phosphoric acid	10%
7664-93-9	Sulfuric acid	12%

US DOT List of Severe Marine Pollutants (172.101 - Appendix B): None

SARA Section 302 Extremely Hazardous Substances (40 CFR 355): 7664-93-9 Sulfuric acid 12%

Sara Section 302 Threshold Planning Quantity:
7664-93-9 Sulfuric acid 12%

SARA Section 313, Toxic Chemicals (40 CFR 372.65):
7664-93-9 Sulfuric acid 12%

SARA Reportable Quantity:

1341-49-7	Ammonium bifluoride	3%
7664-38-2	Phosphoric acid	10%
7664-93-9	Sulfuric acid	12%

Toxic Substances Control Act (TSCA): All components are listed or exempt from the Toxic Substances Control Act.

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1985 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act, and Title 40 of the Code of Federal Regulations, part 372.

7664-93-9	Sulfuric acid	12.1%
-----------	---------------	-------

16. OTHER INFORMATION


Date of Preparation: July 1st, 2016

Revision Date: March 16th, 2017

Hazardous Material Information System (HMIS)

Health	3
Flammability	0
Physical Hazard	1
Personal Protection	D

National Fire Protection Association (NFPA)



HMIS & NFPA Hazard Rating Legend

- * = CHRONIC HEALTH HAZARD
- 0 = INSIGNIFICANT
- 1 = SLIGHT
- 2 = MODERATE
- 3 = HIGH

LEGEND

0 = LEAST 1 = SLIGHT 2 = MODERATE 3 = HIGH 4 = EXTREME

N.D. = NOT DETERMINED N.A. = NOT AVAILABLE N/A = NOT APPLICABLE

DISCLAIMER: While this company believes that the data contained herein are factual and the opinions expressed are based on tests and data believed to be reliable, it is the user's responsibility to determine the safety, toxicity and suitability for his own use of the product described herein. Since the actual use by others is beyond our control, no guarantee, expressed or implied, is made by this company as to the effects of such use, the results to be obtained, or the safety and toxicity of the product, nor does this company assume any liability arising out of use, by others, of the product referred to herein. Nor is this information herein to be construed as absolutely complete since additional information may be necessary or desirable when particular or exceptional conditions or circumstances exist or because of applicable laws or governmental regulations.

REQUIRED SUPPLEMENTAL CONTRACT TERMS: Failure to obtain a property owner's written acceptance of the enclosed Required Supplemental Terms and Conditions for Restoration Contract shall release any and all of the manufacturer's express or implied warranties (including, without limitation, merchantability and fitness for particular purpose) and user shall indemnify and hold manufacturer harmless from all liability cost and expenses arising in any way from use of or contact with this product. All claims of any kind against manufacturer arising from or related to this product in any way shall be decided by binding arbitration in accordance with the Construction Industry Arbitration Rules of the American Arbitration Association. Copyright © 2016

Diedrich Technologies is a division of



Hohmann & Barnard, Inc.
30 Rasons Court | Hauppauge, NY 11788
TEL: 800-645-0616 | FAX: 631-234-0683
EMAIL: weanchor@h-b.com | www.h-b.com

310 Wayto Road | Schenectady, NY 12303 ● TEL: 800-283-3888 | FAX: 518-357-9636
EMAIL: moreinfo@sandellmfg.com | www.diedrichtechnologies.com

310 Wayto Road | Schenectady, NY 12303 ● TEL: 800-283-3888 | FAX: 518-357-9636
EMAIL: moreinfo@sandellmfg.com | www.diedrichtechnologies.com

LEGEND

0 = LEAST 1 = SLIGHT 2 = MODERATE 3 = HIGH 4 = EXTREME

N.D. = NOT DETERMINED N.A. = NOT AVAILABLE N/A = NOT APPLICABLE

DISCLAIMER: While this company believes that the data contained herein are factual and the opinions expressed are based on tests and data believed to be reliable, it is the user's responsibility to determine the safety, toxicity and suitability for his own use of the product described herein. Since the actual use by others is beyond our control, no guarantee, expressed or implied, is made by this company as to the effects of such use, the results to be obtained, or the safety and toxicity of the product, nor does this company assume any liability arising out of use, by others, of the product referred to herein. Nor is this information herein to be construed as absolutely complete since additional information may be necessary or desirable when particular or exceptional conditions or circumstances exist or because of applicable laws or governmental regulations.

REQUIRED SUPPLEMENTAL CONTRACT TERMS: Failure to obtain a property owner's written acceptance of the enclosed Required Supplemental Terms and Conditions for Restoration Contract shall release any and all of the manufacturer's express or implied warranties (including, without limitation, merchantability and fitness for particular purpose) and user shall indemnify and hold manufacturer harmless from all liability cost and expenses arising in any way from use of or contact with this product. All claims of any kind against manufacturer arising from or related to this product in any way shall be decided by binding arbitration in accordance with the Construction Industry Arbitration Rules of the American Arbitration Association.

Copyright © 2015

Diedrich Technologies is a division of



Hohmann & Barnard, Inc.
30 Rasons Court | Hauppauge, NY 11788
TEL: 800-645-0616 | FAX: 631-234-0683
EMAIL: weanchor@h-b.com | www.h-b.com