

### DIEDRICH'S 950 STAIN REMOVER

#### 1. PRODUCT NAME:

DIEDRICH 950 STAIN REMOVER

#### 2. MANUFACTURER:

Diedrich Technologies Inc.  
A Division of Sandell Construction Solutions  
7373 S. 6th Street, Oak Creek, WI 53154  
WI: 800-323-3565 / NY: 800-283-3888  
AL: 877-726-3355  
Internet: [www.diedrichtechnologies.com](http://www.diedrichtechnologies.com)  
[www.sandellmfg.com](http://www.sandellmfg.com)

#### 3. PRODUCT DESCRIPTION:

DIEDRICH 950 Stain Remover is a mild blend of acids, inhibitors and wetting agents for the removal of acid burn and vanadium (green or brown) stains from brick masonry. Diedrich 950 Stain Remover is an effective stain remover for brick siliconed either during manufacturing or after construction. If staining occurs in siliconed brick, Diedrich 940 Iron and Manganese Stain Remover would be the better choice. Diedrich 950 Stain Remover is effective for use on almost all masonry surfaces. Stain control is dependent on many variables in surfaces (polished stone) and job conditions. Corrective measures should be undertaken before cleaning.

#### 4. PRECAUTIONS:

**PERSONNEL:** All workers must be protected with complete body coverage by rubber or polyethylene suits, boots, gloves, face shield and protective headgear. Avoid contact with eyes and skin. Any exposed skin should be covered with a liberal coating of vaseline. Use with adequate ventilation. If used in confined area the use of a respirator with the appropriate filter may be required. When product is to be used on an occupied building, the following steps should be taken to protect occupants from fumes. Close all windows and cover air intakes and exterior air-conditioning vents. Also shut down air handling equipment during application and for 30 minutes following. Avoid wind drift as it may injure passersby or damage vehicles.

KEEP OUT OF THE REACH OF CHILDREN AND ANIMALS.  
**INTERIOR USE:** All metal fixtures in interior should be removed or plastic cover protected as they will be damaged by chemical fumes.

**ADJACENT AREAS:** Protect vegetation, electrical, metal and painted surfaces, anodized aluminum, asphalt roofing, cars and other adjacent items with proper precautions, plastic coverings, and by soaking with water.

#### 5. TEST AREA:

A test patch **MUST** be cleaned prior to full scale cleaning operations. The test patch is necessary to determine compatibility and required end results.

Individual surface types must be tested. Inspection of the test areas should occur after the surface has thoroughly dried. The test patch should be available for inspection and approval, then remain as the standard for the project.

#### 6. APPLICATION:

Apply concentrated Diedrich 950 Stain Remover full strength to the surface being cleaned. Application should be to a dry surface with a synthetic bristle brush, or the most effective method of application is with the DIEDRICH ACID EXPRESS PUMP, an acid-resistant airless low pressure sprayer. Allow 10 to 15 minute dwell time, or until the stains have disappeared. If stains are not removed in 10 to 15 minutes, re-apply 950 Stain Remover and allow another 10 to 15 minute dwell time and rinse with fresh water. Application of rinse water should be with pressure washing equipment, fitted with a 15°, 25° or 40° fan type tip. Equipment providing 500 p.s.i. at 3 to 5 gallons per minute will give the best results. If 950 Stain Remover is used on an interior surface, following the rinse the surface must be neutralized with a solution consisting of 1 part household ammonia and 5 parts water. Application can be with sponges or bristle scrub brushes.

#### 7. COVERAGE:

1 gallon of the Diedrich 950 Stain Remover full-strength will cover approximately 150 sq.ft. of surface. Area coverage can be increased with dilution.

#### 8. AVAILABILITY:

Diedrich products are available through a network of over 1400 distributors and 2100 contractors located throughout the United States, Canada, Mexico and Europe.

#### 9. WARRANTY:

ALWAYS USE A TEST SAMPLE TO DETERMINE DESIRED RESULTS. PRODUCT FREEZES BELOW 32°F, AND MAY BE ADVERSELY AFFECTED BY COLD WEATHER. DIEDRICH TECHNOLOGIES INC., warrants that the product will conform to the description and specifications set forth on the product label and will be free from defects in material and workmanship. The exclusive remedy of the Buyer in the event that the product does not so conform shall be the replacement of the product. This warranty is expressly made in lieu of any and all other warranties, expressed or implied, including the warranties of merchantability and fitness, and Diedrich Technologies Inc. shall not be liable for any loss or damage, directly or indirectly, arising from the use of such merchandise

or for consequential or incidental damages.

While Diedrich Technologies Inc. believes that the data contained herein is accurate and the information is based on test and data believed to be reliable, it is the user's responsibility to determine the safety, toxicity and suitability for his own use of the product described herein. Manufacturer shall not be responsible for any contamination, or related testing or removal costs resulting from use of this lead-free product on any material containing lead or toxic or environmentally hazardous substances. Since the actual use, by others, is beyond our control, no guarantee, expressed or implied, is made by Diedrich Technologies Inc. as to the effects of such use, the results to be obtained, or the safety and toxicity of the product referred to herein. Nor is the information herein to be construed as absolutely complete since additional information may be necessary or desirable when particular conditions or circumstances exist or because of applicable laws or governmental regulations. All claims of any kind against manufacturer arising from or related to this product in any way shall be decided by binding arbitration in accordance with the Construction Industry Arbitration rules of the American Arbitration Association.

Copyright © 1993 / Revised 09/2008

DIEDRICH TECHNOLOGIES, INC.  
A Division of Sandell Construction Solutions  
WI: 800.323.3565  
NY: 800.283.3888  
AL: 877.726.3355  
View our full line of products online:  
[www.diedrichtechnologies.com](http://www.diedrichtechnologies.com)

ENVIRONMENTAL PROTECTION SYSTEM:  
USE DIEDRICH NEUTRA-SOAK "A" (FOR ACIDS), WHICH IS A DRY ABSORBENT COMPOUND, FOR SPILLAGE AND TO DIKE/CONTAIN AND COLLECT WASH-OFF RESIDUE FOR SAFER DISPOSAL AND TO ADDRESS LOCAL ENVIRONMENTAL REQUIREMENTS