

DIEDRICH OIL STAIN REMOVAL KIT

DIRECTIONS

DIEDRICH OIL STAIN REMOVAL KIT CAN SAFELY AND EASILY BE USED ON VERTICAL AS WELL AS HORIZONTAL SURFACES. NO DAMAGING SCRUBBING OR ABRASIVE ACTION IS NECESSARY. IT CAN BE USED ON BRICK, BLOCK, CONCRETE, MARBLE, SANDSTONE, LIMESTONE, STUCCO, GRANITE, TERRA COTTA AND SLATE. IF USED ON A PAINTED, SEALED OR TREATED SURFACE, THESE MAY BE ALSO REMOVED AT THE SAME TIME AS THE GREASE OR OIL STAIN. TEST PATCHES MUST BE CONDUCTED TO DETERMINE SUITABILITY AND RESULTS. IT MUST BE NOTED THAT 100% REMOVAL OF ALL STAINS IS NOT ALWAYS POSSIBLE. DEEP SEATED STAINS MAY PROVE DIFFICULT. COVERAGE: 1 1/2 TO 2 SQ. FT. PER KIT. EXEMPT OF VOC REGULATIONS.

PROCEDURE

COMBINE PART A - SPECIAL ODORLESS SOLVENT GAUGING LIQUID AND PART B (PLASTIC BAG) 2¼ lbs. (NON-ACIDIC/NON-CAUSTIC) POUltICE POWDER IN THE 1 GALLON PAIL SUPPLIED. MIX THOROUGHLY UNTIL A THICK PASTE CONSISTENCY IS ACHIEVED. DO NOT PRE-MIX THESE MATERIALS; THEY SHOULD BE COMBINED JUST BEFORE USE. MIXING HOURS BEFORE OR THE DAY BEFORE USE MAY RENDER THE MIXTURE INEFFECTIVE. SURFACE AND AIR TEMPERATURES SHOULD BE AT LEAST 40°F.

APPLICATION

APPLY TO STAINED AREA WITH A TROWEL OR BROAD KNIFE AT 1/4 TO 1/2 INCH THICK, DEPENDING ON THE SEVERITY OF THE STAIN. DWELL TIME WILL VARY WITH SEVERITY OF THE STAIN. MOST STAINS MAY BE REMOVED WITHIN 24 HOURS. MORE SEVERE AND DEEP SEATED STAINS MAY REQUIRE UP TO 48 HOURS TO REMOVE AND A POSSIBLE SECOND APPLICATION. TO SLOW DOWN DRYING OF THE PASTE, (WHICH WILL BE NECESSARY FOR LONGER DWELL TIMES ON DEEP SEATED STAINS) PLACE A PIECE OF PLASTIC SHEETING OR ALUMINUM FOIL OVER THE TREATED AREA AND TAPE DOWN EDGES.

USE IN WELL VENTILATED AREAS AND KEEP AWAY FROM SPARKS, OPEN FLAMES SUCH AS PILOT LIGHTS AND FIRE. IT MUST BE REMEMBERED, THE GAUGING LIQUID WHILE NOT FLAMMABLE IS COMBUSTIBLE AND CARE MUST BE TAKEN. KEEP AWAY FROM CHILDREN AND ANIMALS.

REMOVAL

REMOVE PLASTIC/FOIL/TAPE IF USED AND LET DRY. SCRAPE OFF DRIED PASTE. RINSE AREA WITH FRESH WATER PREFERABLY WITH A PRESSURE WASHER. IF PRESSURE WASHING IS NOT FEASIBLE, A GARDEN HOSE CAN BE USED OR SCRUB BRUSH AND FRESH WATER. REMOVED PASTE SHOULD BE PLACED IN AN OPEN METAL CONTAINER UNTIL SOLVENT TOTALLY EVAPORATES (APPROX. 1-2 DAY). UPON COMPLETE EVAPORATION THE MATERIAL CAN THEN BE DISPOSED OF.

WARRANTY:

ALWAYS USE A TEST SAMPLE TO DETERMINE DESIRED RESULTS. PRODUCT PERFORMANCE MAY BE ADVERSELY AFFECTED BY COLD WEATHER. DIEDRICH TECHNOLOGIES INC. warrants that the product will conform to the description and specifications set forth on the product label and will be free from defects in material and workmanship. The exclusive remedy of the Buyer in event that the product does not so conform shall be the replacement of the product. This warranty is expressly made in lieu of any and all other warranties, expressed or implied, including the warranties of merchantability and fitness, and Diedrich Technologies Inc., shall not be liable for any loss or damage, directly or indirectly, arising from the use of such merchandise or for consequential or incidental damages.

While Diedrich Technologies Inc., believes that the data contained herein is accurate and the information is based on test and data believed to be reliable, it is the user's responsibility to determine the safety, toxicity and suitability for his own use of the product described herein. Manufacture shall not be responsible for any contamination, or related testing or removal costs resulting from use of this lead-free product on any material containing lead or other toxic or environmentally hazardous substances. Since the actual use, by others, is beyond our control, no guarantee, expressed or implied, is made by Diedrich Technologies Inc. as to the effects of such use, the results to be obtained, or the safety and toxicity of the product referred to herein. Nor is the information herein to be construed as absolutely complete since additional information may be necessary or desirable when particular conditions or circumstances exist or because of applicable laws or governmental regulations. All claims of any kind against manufacturer arising from or related to this product in any way shall be decided by binding arbitration in accordance with the Construction Industry Arbitration Rules of the American Arbitration Association.

DIEDRICH TECHNOLOGIES, INC.

A Division of Sandell Construction Solutions

WI: 800.323-3565

NY: 800.283.3888

AL: 877.726-3355

View our full line of products online: www.diedrichtechnologies.com